

INKCUPS

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Print date: 04.05.2018

J Primer

Page 1 of 7

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Metal Primer

Further trade names

BO 5209488 Bohle glass/metal primer for UV-bonding, 100 ml

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture

metal adhesion promoter

1.3. Details of the supplier of the safety data sheet

Company name: INKCUPS NOW CORPORATION
Street: 310 Andover
Place: Danvers, MA. 01923
Telephone: 978.646.8980 Fax: 978.646.8981
e-mail: compliance@inkcups.com

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Indications of danger: F - Highly flammable, Xi - Irritant
R phrases:
Highly flammable.
Irritating to eyes.
Vapours may cause drowsiness and dizziness .

GHS classification

Hazard categories:
Flammable liquid: Flam. Liq. 2
Serious eye damage/eye irritation: Eye Irrit. 2
Specific target organ toxicity - single exposure: STOT SE 3
Hazard Statements:
Highly flammable liquid and vapour.
Causes serious eye irritation.
May cause drowsiness or dizziness.

2.2. Label elements

Hazardous components which must be listed on the label

propan-2-ol; isopropyl alcohol; isopropanol

Signal word: Danger

Pictograms: GHS02-GHS07



Hazard statements

H225 Highly flammable liquid and vapour.
H319 Causes serious eye irritation.
H336 May cause drowsiness or dizziness.

Precautionary statements

P210	Keep away from heat/sparks/open flames/hot surfaces. - No smoking.
P233	Keep container tightly closed.
P240	Ground/bond container and receiving equipment.
P241	Use explosion-proof electrical/ventilating/lighting equipment.
P242	Use only non-sparking tools.
P243	Take precautionary measures against static discharge.
P261	Avoid breathing dust/fume/gas/mist/vapours/spray.
P271	Use only outdoors or in a well-ventilated area.
P280	Wear protective gloves/protective clothing/eye protection/face protection.
P303+P361+P353	IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.
P304+P340	IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.
P312	Call a POISON CENTER or doctor/physician if you feel unwell.
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P337+P313	If eye irritation persists: Get medical advice/attention.
P235	Keep cool.
P403+P233	Store in a well-ventilated place. Keep container tightly closed.
P405	Store locked up.

Additional advice on labelling

The product is classified and labelled in accordance with EC directives or respective national laws.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Hazardous components

EC No	Chemical name	Quantity
CAS No	Classification	
Index No	GHS classification	
REACH No		
200-661-7	propan-2-ol; isopropyl alcohol; isopropanol	50-100 %
67-63-0	F - Highly flammable, Xi - Irritant R11-36-67	
603-117-00-0	Flam. Liq. 2, Eye Irrit. 2, STOT SE 3; H225 H319 H336	

Full text of R and H phrases: see Section 16.

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

Take off all contaminated clothing immediately. Remove from exposure, lie down. Move to fresh air. Artificial respiration and/or oxygen may be necessary.

After inhalation

Move to fresh air. Consult a physician after significant exposure. If victim is unconscious but breathing: Victim to lie down in the recovery position, cover and keep him warm. Call a physician immediately.

After contact with skin

Wash off immediately with soap and plenty of water. If skin irritation persists, call a physician.

After contact with eyes

Rinse thoroughly with plenty of water, also under the eyelids. If eye irritation persists, consult a specialist.

I N K C U P S

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Print date: 04.05.2018

J Primer

Page 3 of 7

After ingestion

Clean mouth with water and drink afterwards plenty of water. If swallowed, do not induce vomiting - seek medical advice.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

water spray alcohol-resistant foam dry chemical carbon dioxide (CO₂)

Extinguishing media which must not be used for safety reasons

high volume water jet

5.2. Special hazards arising from the substance or mixture

Fire may cause evolution of: Carbon monoxide

5.3. Advice for firefighters

In the event of fire, wear self-contained breathing apparatus. Standard procedure for chemical fires.

Additional information

Use water spray to cool unopened containers.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Use personal protective equipment. Keep people away from and upwind of spill/leak. Ensure adequate ventilation. Keep away from heat and sources of ignition. Avoid contact with skin and eyes.

6.2. Environmental precautions

Do not flush into surface water or sanitary sewer system. Local authorities should be advised if significant spillages cannot be contained.

6.3. Methods and material for containment and cleaning up

Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust). Ensure adequate ventilation.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

Handle and open container with care. Provide sufficient air exchange and/or exhaust in work rooms.

Advice on protection against fire and explosion

Use explosion-proof equipment. Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapours). Vapours are heavier than air and may spread along floors. Vapours may form explosive mixtures with air. Keep away from heat and sources of ignition. Do not smoke.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Keep containers tightly closed in a cool, well-ventilated place.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

INKCUPS

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Print date: 04.05.2018

J Primer

Page 4 of 7

Exposure limits (EH40)

CAS No	Substance	ppm	mg/m ³	fibres/ml	Category	Origin
67-63-0	Propan-2-ol	400	999		TWA (8 h)	WEL
		500	1250		STEL (15 min)	WEL

8.2. Exposure controls

Occupational exposure controls

Even in case of a full release, due to the small amount of substances present, it is not expected that exposure limits will be reached. However it is the duty of the user to verify this and follow given exposure limits at the workplace.

Protective and hygiene measures

Avoid contact with skin, eyes and clothing. Provide adequate ventilation. Take off all contaminated clothing immediately. Keep away from food, drink and animal feedingstuffs. When using do not eat or drink. Do not smoke. Wash hands before breaks and at the end of workday .

Respiratory protection

In case of insufficient ventilation, wear suitable respiratory equipment.

Hand protection

solvent-resistant gloves (butyl-rubber)

Eye protection

tightly fitting safety goggles

Skin protection

impervious clothing

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state: liquid
Colour: clear
Odour: alcoholic

Test method

pH-Value (at 20 °C): neutral

Changes in the physical state

Melting point: -89,5 °C
Boiling point: 82 °C
Flash point: 12 °C

Explosive properties

In use, may form flammable/explosive vapour-air mixture.

Lower explosion limits: 2 vol. %
Upper explosion limits: 12 vol. %
Ignition temperature: 425 °C
Vapour pressure: 48 hPa
(at 20 °C)
Density (at 20 °C): 0,785 g/cm³
Water solubility: soluble
(at 20 °C)
Viscosity / dynamic: 2,43 mPa·s
(at 20 °C)

Vapour density:
(at 20 °C)

2

SECTION 10: Stability and reactivity

10.4. Conditions to avoid

No decomposition if used as directed.

10.5. Incompatible materials

strong acids and oxidizing agents

10.6. Hazardous decomposition products

None known.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity

LD50/oral/rat = 5840 mg/kg

Irritation and corrosivity

Mild eye irritation

Mild skin irritation

Severe effects after repeated or prolonged exposure

Exposure to component solvent vapour concentrations in excess of the stated occupational exposure limit may result in adverse health effect, such as mucous membrane and respiratory system irritation and adverse effect on kidney, liver and central nervous. Repeated or prolonged contact with the preparation may cause removal of natural fat from the skin resulting in non-allergic contact dermatitis and absorption through the skin.

SECTION 12: Ecological information

12.1. Toxicity

Acute fish toxicity = LC50/48h/guppy = 8970 mg/l

Toxicity to daphnia LC50/48h/daphnia = > 1000 mg/l

Toxicity to algae LC50/96h/algae = > 1000mg/l

12.2. Persistence and degradability

Readily biodegradable, according to appropriate OECD test.

12.4. Mobility in soil

The product evaporates readily.

Further information

Do not let product enter drains.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Advice on disposal

In accordance with local and national regulations.

Waste disposal number of waste from residues/unused products

080111 WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS; wastes from MFSU and removal of paint and varnish; waste paint and varnish containing organic solvents or other dangerous substances
Classified as hazardous waste.

SECTION 14: Transport information

Land transport (ADR/RID)

14.1. UN number: UN1219
14.2. UN proper shipping name: ISOPROPANOL (ISOPROPYLALCOHOL)
14.3. Transport hazard class(es): 3
14.4. Packing group: II
Hazard label: 3



Classification code: F1
Special Provisions: 601
Limited quantity: 1 L
Transport category: 2
Hazard No: 33
Tunnel restriction code: D/E

Other applicable information (land transport)

E2

Inland waterways transport (ADN)

14.1. UN number: UN1219
14.2. UN proper shipping name: ISOPROPANOL (ISOPROPYL ALCOHOL)
14.3. Transport hazard class(es): 3
14.4. Packing group: II
Hazard label: 3



Classification code: F1
Special Provisions: 601
Limited quantity: 1 L

Other applicable information (inland waterways transport)

E2

Marine transport (IMDG)

14.1. UN number: UN1219
14.2. UN proper shipping name: ISOPROPANOL (ISOPROPYLALCOHOL)
14.3. Transport hazard class(es): 3
14.4. Packing group: II
Hazard label: 3



Special Provisions: -
Limited quantity: 1 L
EmS: F-E, S-D

Other applicable information (marine transport)

E2

Air transport (ICAO)

14.1. UN number: UN1219
14.2. UN proper shipping name: ISOPROPANOL (ISOPROPYLALCOHOL)
14.3. Transport hazard class(es): 3
14.4. Packing group: II
 Hazard label: 3



Special Provisions: A180
 Limited quantity Passenger: 1 L
 IATA-packing instructions - Passenger: 353
 IATA-max. quantity - Passenger: 5 L
 IATA-packing instructions - Cargo: 364
 IATA-max. quantity - Cargo: 60 L

Other applicable information (air transport)

E2

Y341

14.5. Environmental hazards

Dangerous for the environment: no

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

National regulatory information

SECTION 16: Other information

Full text of R phrases referred to under Sections 2 and 3

11 Highly flammable.
 36 Irritating to eyes.
 67 Vapours may cause drowsiness and dizziness.

Full text of H statements referred to under Sections 2 and 3

H225 Highly flammable liquid and vapour.
 H319 Causes serious eye irritation.
 H336 May cause drowsiness or dizziness.

Further Information

The information is based on present level of our knowledge. It does not, however, give assurances of product properties and establishes no contract legal rights. The receiver of our product is singularly responsible for adhering to existing laws and regulations.

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)